

aleddra **LED Lighting**

Module Flood Light FL 675 Series Instruction Manual



675 Series:
400W, 600W



Dimensions:

400W: L:228in W:293in H:64in

600W L:289in W:293in H: 64in


WARNING: RISK OF FIRE - Lamps are hot. Keep combustible material an adequate distance from hot parts.

WARNING:
RISK OF Electric Shock - To avoid electric shock, serious injury or death, be certain that all electrical power is disconnected from the supply branch circuit conductors before installing or maintaining this fixture. This product must be installed and maintained in accordance with the applicable installation codes by a person familiar with the construction and operation of the product and the hazards involved. Avoid direct eye exposure to the light source when light is on.

IMPORTANT INSTALLATION NOTES:

1. All work should be done by a qualified electrician.
2. Fixture must be installed in accordance with the National Electric Code and all applicable local codes and ordinances.
3. The use of safety protection (ie eye protection, and safety gloves) is recommended.
4. To reduce the risk of electric shock, insure electricity has been turned off at the circuit breaker or fuse box before beginning.
5. This fixture is for outdoor use only and should not be used in areas with limited ventilation or high ambient temperatures.
6. Lamp should never be covered with anything to allow for heat dissipation.
7. Proper grounding is required to ensure safety.
8. All installation and safety instructions should be followed for full warranty coverage.

Instructions for installation




ADJUSTING FIXTURE ANGLE:

1. Unscrew the screw of the rotating bracket.
2. Adjust to a suitable angle, then tighten the screw.

Brown: Live Wire

Yellow Green: Ground Wire

Blue: Neutral Wire



WIRING:

1. Check that voltage is compatible with fixture ballast. Use code compliant connectors for all electrical connections.
2. Connect the black fixture lead to the black supply lead.
3. Connect the white fixture lead to the white supply lead.
4. Connect the green fixture lead to the green supply lead.

MOUNTING:

1. Turn off the power and make sure the wall can sustain the burden of the weight before installing the lamp.
2. Secure the lamp so that it won't fall.
3. Do not cover the lamp.
4. Secure with M10 screws.
5. Turn off all power to the lamp, and make sure the ground line is well secured before turning power on.

SAVE THESE INSTRUCTIONS

Aleddra LED Lighting 2210
Lind Ave. SW Suite 109
Renton WA, 98057