



Specifications

Lens Type	clear
Driver Type	external driver
Input Voltage	100V-277VAC (50-60Hz)
Output Voltage	36V DC
Efficacy	> 95 LPW (clear lens)
Color	30K, 35K, 40K, 45K, 50K
CRI	> 80
Operating Temp.	-20°F-122°F
Power Factor	> .90
Beam Angle	170°
Warranty	5-year

Ordering Information

Product #	Length	Lens	Color
LLT-4-FR-C-22W-35K	4-ft	Clear	3500K
LLT-4-FR-C-22W-40K	4-ft	Clear	4000K
LLT-4-FR-C-22W-50K	4-ft	Clear	5000K
LLT-5-FR-C-22W-35K	4-ft	Clear	3500K
LLT-5-FR-C-22W-40K	5-ft	Clear	4000K
LLT-5-FR-C-22W-50K	5-ft	Clear	5000K
LLT-6-FR-C-30W-35K	6-ft	Clear	3500K
LLT-6-FR-C-30W-40K	6-ft	Clear	4000K
LLT-6-FR-C-30W-50K	6-ft	Clear	5000K

Features

- Qualifies for Utility Rebates
- IP65 rating for moisture proof
- LED alternative for refrigerator lighting
- External driver included
- National groceries, supermarkets, and convenience stores are the perfect target audience for the Cooler Tube

Product Compliance & Certifications:

- cULus
- DLC

Description

Aleddra, with its strong industry reputation with the EasiRetrofit® LED tube for T12/T8 replacements, is now offering an LED alternative for refrigerator lighting.

The Cooler Tube is designed with a 170 degree beam angle, meeting the needs of merchandise lighting on both sides of the LED light, while maintaining a high efficacy at 95 lm/w and a power factor 0.90.

National groceries, supermarkets, and convenience stores are the perfect target customer for the CoolerTube. It is used in coolers and refrigerators.