HID Replacement LED Filament Lamp







Specifications

Wattage	40W,	55W	, 65W,	85W

Color Temperature 5000K

Beam Angle 360°

Input Voltage 120-277 VAC

Power Factor 0.9

CRI >80

Efficacy 180 LM/W

Dimming Non-dimmable

Operating Temp. -4° to 113° F

Rated Life 25,000 hrs

Warranty 2-year

Ordering Information

Product Model #	HID Equivalent Highest Wattage (W)	Lumen
HiLED 40W/ED28/EX39/5000K	250W	7200lm
HiLED 55W/ED37/EX39/5000K	400W	10010lm
HiLED 65W/ED37/EX39/5000K	400W	12025lm
HILED 85W/ED37/EX39/5000K	450W	15300lm

^{*} Other color and wattage available made to order

Features

- Great heat dissipation
- Light weight
- Same form factor as HID lamps
- Easy to install and operate
- Type B installation (ballast bypass)
- Energy savings of more than 75% over conventional HID metal halide lamps


Product Compliance & Certifications:

ETL Listed

Description

The new HID Replacement LED Filament Lamps offer an easy and short payback solution to replace High Intensity Discharge (HID) lamps. They bring all the energy efficiency and long-life benefits of LED to HID replacement, while providing instant savings from a low initial investment. These lamps are designed with an optimal lamp size as well as light distribution with a familiar look and feel as conventional HID lamps. What sets them apart is the innovative High-Power LED filament technology enclosed in a glass bulb, ensuring a distinctive lighting experience. They are easily retrofit for outdoor and indoor applications.

Dimensions




40W:

A - 90mm/3.54inch B - 235mm/9.25inch 55W:

A - 120mm/4.72inch

B - 285mm/11.22inch



65W:

A - 120mm/4.72inch B - 292mm/11.5inch 85W:

A - 120mm/4.72inch

B - 292mm/11.5inch

^{** 65}W and 85W models are rated for OPEN fixtures only.